



**NOTE:**

Railings are required on decks 30 inches or more above grade

Hand grips are required on stairs with four (4) or more steps including the deck

Deck Dimensions: \_\_\_\_\_ X \_\_\_\_\_ ; Height Above Grade: \_\_\_\_\_ Feet

Deck Support: Free Standing \_\_\_\_\_ OR Attached to Main Structure \_\_\_\_\_

Support Pad/Footing Size: \_\_\_\_\_ ; Footing Depth Below Grade: \_\_\_\_\_ Inches  
 See Footing Table on Reverse Side

Support Post Size: \_\_\_\_\_ X \_\_\_\_\_ ; Post Spacing: \_\_\_\_\_ Feet.  
 Max Post Height Above Grade:  
 4 x 4's = 6'; 4 x 6's = 10'; 6 x 6's = 12'; Over 12' Height = Must Be Engineered

Support Beam(s) Size: Dbl \_\_\_\_\_ X \_\_\_\_\_ ; Beam Span between Posts: \_\_\_\_\_ Feet  
 See Beam Span Table on Reverse Side

**\*\*BEAMS MUST BE SADDLED ONTO POSTS\*\* See Attachment Chart**

Deck Joist Size: \_\_\_\_\_ X \_\_\_\_\_ ; Deck Joist Span Between Beams: \_\_\_\_\_ ;

Deck Joist Spacing: \_\_\_\_\_ Inches

Type & Size Deck Planking: \_\_\_\_\_